

COIN CHANGER AND RECYCLER

CURRENZA C²

6-tubes coin changer with
Payout Redundancy System

REDUCE YOUR MACHINE DOWNTIME AND INCREASE REVENUES

Currenza C² with PRP (Payout Redundancy Protection) system is specifically designed for the operator: it minimizes machine down time and assures high safety in every applications, making the vending machine more profitable and reliable.

FEATURES

- Acceptance and payout of all circulation coins (also 0,01 €)
- Payout combination optimization to meet each machine's planogram and site users payment behavior
- Modular cassette structure for great freedom in tube configuration
- Easy and fast programming with use friendly intuitive menu
- High payout speed of up to 6 coins per second and acceptance speed of up to 3 coins/second
- Easy access to validation and sorting area for maintenance
- MFT technology providing a more secure coin validation, sensor system to measure up to 40 different parameters

PRP System (Payout Redundancy Protection) 6 tubes cassette and 3 independent motors for high payout safety and the minimization of down time



OPTIONAL ACCESSORIES

External box to connect Currenza C² to small automatic and semi-automatic vending machines

VERSIONS

- Blue (EXE, MDB) with display and keys
- White (MDB) without keys or display

TECHNICAL SPECIFICATION	
DIMENSIONS (H X W X D)	137.75 x 377.10 x 80.00 mm
POWER SUPPLY	BDV: 18V ÷ 43V DC MDB: 18V ÷ 43V DC Battery MDB: 11V ÷ 43V Executive version: 24V AC
POWER CONSUMPTION	Stand-by mode: 2.5W max Coin payout: 16.0V max - 48W max with 3 motors Coin acceptance: 16.0VW max
OPERATING TEMPERATURE	-25°C ÷ +80°C

TUBES COMBINATIONS						
DIAMETER (MM)	TUBES					
	A	B	C	D	E	F
29.0 - 32.5	■					
26.5 - 29.0	■		■			■
24.5 - 26.5	■		■		■	■
23.0 - 24.5	■	■	■	■	■	■
21.5 - 23.5	■	■	■	■	■	■
20.0 - 21.5		■	■	■	■	■
18.5 - 20.00		■	■	■	■	
17.0 - 18.5		■		■	■	
16.0 - 17.0		■		■	■	
15.0 - 16.0		■		■		

TUBES CAPACITY	
COINS	TUBE CAPACITY
2 €	72
1 € - 0.50 €	69-67
0.20 €	75
0.10 € - 0.02 €	83-97
0.05 €	95
0.01 €	97

